

Technical data sheet.

Lehm Fixativ - Clay fixing agent

Product Description

Lehm Fixativ is a clay fixing agent and is a ready-to-use diluted silicate primer to increase the abrasion and surface strength of clay plasters and clay fillers.

Information

This product data sheet contains advice to the best of our knowledge and replaces all previous product data sheets. Its content, however, is not legally binding

> Technical data and characteristics

Consumption	approx. 0.1 - 0.3 l per m ²
-------------	--

> Logistics and safety instructions

Form of delivery	10 litre canister
Storage	Clay fixing agent can be stored for at least 12 months in appropriate conditions.
Safety instructions	Protect your eyes and skin from splashes. EU limit value for this product: Cat. (A/h) 30 g/l (2010) This product contains a maximum of 1.0 g/l VOC

> Properties

Minimised emissions, free from plasticisers and solvents. For consolidating mineral substrates and levelling of strongly or unevenly absorbent surfaces.

> Processing and processing time

Clay fixing agent must be used undiluted. Carefully cover stone, glass, metal, window panes, cornices, etc. To achieve deeper penetration, apply twice "wet-on-wet". Avoid re-coating already dried surfaces due to the risk of fogging.

> Important Notes

- Ensure sufficient ventilation of rooms during and after use
- During application, the substrate and ambient temperature must not be below +8 °C
- Do not admix foreign material
- Clean tools with water immediately after use
- Store in a cool but frost-free place

For further information, please contact:

CASEA GmbH
Pontelstraße 3
99755 Ellrich
Germany
T +49 36332 89-100
F +49 36332 89-202
info@casea-gips.de
casea-gips.de

A company of the
REMONDIS Group